

Skeie | Solist Love seat™

TECHNICAL SPECIFICATION

skeie®

Skeie Seating AS,
Vestre Svanholmen 13
N-4313 Sandnes, Norway
—
E: seating@skeie.com
www.skeie.com

Reg.No. NO913369947MVA

DIMENSIONS

High back, 1040 mm: C/C 1050, 1070, 1090, 1120mm.
Reclinable mechanism for seat and back.

FRAME CONSTRUCTION

ST-37 steel alloy.
Supporting steel structure: 25 x 50 x 3 mm.
Standard floor fixing: Flat iron of 70 x 7 mm
Powder coated steel in standard RAL colors.
Floor fixing every other chair.
The chair is suitable for fixing in the riser, on flat floor and in straight or curved rows.
All fixings in chair are metal to metal.

SEAT

Cold moulded polyurethane foam w/ integrated 19 x 2 mm steel frame, thickness 110 mm.
Upholstery sewn to measurements and easily removable with zipper solution.

SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steel frame, thickness 110 mm.
Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Cold moulded polyurethane foam with integrated steel frame, optional widths are 70, 90, 110, 140 mm depending on the seat width.
Cupholder or table mounted to steel frame on armrest available.

ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.
Row and seat numbers are available.
Can be delivered without the reclining functionality.
Other qualities and measurements are available upon request.