

Skeie | Sonate LuxTM

TECHNICAL SPECIFICATION

skeie®

Skeie AS, P.O. Box 4,
N-4301 Sandnes, Norway

T +47 51 97 45 00

F +47 51 97 45 01

E seating@skeie.com

www.skeie.com

Reg.No. NO981505409MVA

DIMENSIONS

High back, 985mm: C/C 600mm, 630mm

Extra high back, 1110mm: C/C 600mm, 630mm

Reclinable mechanism for seat and back. Steeltube \varnothing 25 x 2 mm w/ nylon bush and external spring.

FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 25 x 50 x 3 mm.

Powder coated steel in standard RAL colors.

Floor fixing every other chair.

Fixing in straight or slightly curved rows.

All fixings in chair are metal to metal.

SEAT

Cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 130 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness 160 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Cold moulded polyurethane foam with integrated steelframe, width 110mm.

ALTERNATIVE W/ TABLE

Wood tabletop fixed between chairs. The front of the table can be upholstered in fabrics or leather.

Standard width is 300mm, which can be adjusted based on requirements.

ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Row and seatnumbers are available.

Other qualities and measurements are available upon request.