

# Skeie | Sonate Planet™

## TECHNICAL SPECIFICATION

### DIMENSIONS

Height backrest, 965mm:

C/C 560mm - 670mm.

Reclinable mechanism for seat and back. Steeltube  $\varnothing$  25 x 2 mm w/ nylon bush and external spring.

### FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 25 x 50 x 3 mm.

Standard floor fixing: Flatiron of 70 x 7 mm fixed to rear of the tread.

Powder coated steel in standard RAL colors.

Floor fixing every other chair.

The chair is suitable for fixing in the riser, on flat floor and in straight or curved rows.

All fixings in chair are metal to metal.

### SEAT

Cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 120 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

### SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness 110 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

### ARMREST

Cold moulded polyurethane foam with integrated steelframe, widths are 50, 70, 110, 140 mm depending on the seat width.

Cupholder or table mounted to steelframe on armrest available.

Hana armrests in wood available; width 60, 80, 120, 150 mm depending on the row layout.

Available with wood armrests and sidepanels for row-end chairs, and without sidepanels for middle seats.

### OPTIONAL W/ FOLDABLE WRITING TABLET

Top of armrest: Solid wood in beech or birch.

Foldable writing tablet enclosed in armrest, Notis A, 12 mm plywood with laminate top and lacquered edges.

Armrest sidepanel is 6,5 mm plywood covered with fabric fixed to steelframe of armrest.

### ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Row and seatnumbers are available.

Other qualities and measurements are available upon request.