

Skeie | Sonate ReclinerTM

TECHNICAL SPECIFICATION

skeie®

Skeie AS, P.O. Box 4,
N-4301 Sandnes, Norway

T +47 51 97 45 00
F +47 51 97 45 01

E seating@skeie.com

www.skeie.com

Reg.No. NO981505409MVA

DIMENSIONS

Low back, 965mm: C/C 560mm, 580mm, 600mm, 640mm
High back, 1040mm: C/C 560mm, 580mm, 600mm, 640mm
High back, 1040mm (builds over armrest): C/C 560mm, 580mm, 600mm, 640mm
Extra high back, 1120mm (builds over armrest): C/C 560mm, 580mm, 600mm, 640mm
Reclinable mechanism for seat and back. Steeltube \varnothing 25 x 2 mm w/ nylon bush and external spring.

FRAME CONSTRUCTION

ST-37 steel alloy.
Supporting steel structure: 25 x 50 x 3 mm.
Standard floor fixing: Flatiron of 70 x 7 mm fixed to rear of the tread.
Powder coated steel in standard RAL colors.
Floor fixing every other chair.
The chair is suitable for fixing in the riser, on flat floor and in straight or curved rows.
All fixings in chair are metal to metal.

SEAT

Cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 120 mm.
Upholstery sewn to measurements and easily removable with zipper solution.

SEATBACK

Cold moulded polyurethane foam with integrated 22 x 2 mm steelframe, thickness 110 mm.
Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Cold moulded polyurethane foam with integrated steelframe, optional widths are 70, 90, 110mm depending on the seat width.
Cupholder or table mounted to steelframe on armrest available.
Hana armrests in wood available, width 80, 100, 120 mm for C/C 550, 560, 580, 600 mm.
Available with wood armrests and sidepanels for row-end chairs, and without sidepanels for middle seats.

ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.
Row and seatnumbers are available.
Foldable writing tablet in armrest available, Notis A, 12 mm plywood w/ laminate top available.
Can be delivered with Gimle table in 19mm MDF with lacquered plywood or laminate. Oval table is mounted on a steel frame on the armrest.
Can be delivered without the reclining functionality.
Other qualities and measurements are available upon request.