

# Skeie | Sonate Sofa™

## TECHNICAL SPECIFICATION

### DIMENSIONS

High back, 1050mm.:

C/C 1200 mm.

### FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure.

Standard floor fixing: Flatiron of 70 x 7 mm fixed to rear of the tread.

Powder coated steel in standard RAL colors.

Floor fixing every other chair.

The chair is suitable for fixing in the riser, on flat floor and in straight or slightly curved rows.

All fixings in chair are metal to metal.

### SEAT

Cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 120 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

### SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness 70 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

### ARMREST

Cold moulded polyurethane foam with integrated steelframe, optional widths are 90 and 110 mm.

Cupholder mounted to steelframe on armrest available.

Hana armrests in wood available: width 100 or 120 mm.

Available with wood armrests and sidepanels for row-end chairs, and without sidepanels for middle seats.

### ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Row and seatnumbers are available.

Can be delivered with Gimle table in 19mm MDF with lacquered plywood or laminate. Oval table is mounted on a steel frame on the armrest.

Other qualities and measurements are available upon request.