

# Skeie | Sonate Tip-Up™

TECHNICAL SPECIFICATION

Skeie AS, P.O. Box 4,  
N-4301 Sandnes, Norway

T +47 51 97 45 00

F +47 51 97 45 01

E [seating@skeie.com](mailto:seating@skeie.com)

[www.skeie.com](http://www.skeie.com)

Reg.No. NO981505409MVA

## DIMENSIONS

Low back, 955mm:	C/C 520mm, 550mm, 560mm, 580mm, 600mm, 630mm, 640mm, 670mm
High back, 1040mm:	C/C 520mm, 560mm, 600mm, 630mm, 640mm, 670mm
High back (extended width):	C/C 560mm, 600mm, 630mm, 670mm

## FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 60 x 40 x 3 mm.

Standard floor fixing: 240 x 156 x 7 mm steelbracket fixed to the rear of the tread.

Powder coated steel in standard RAL colors.

The chair is suitable for fixing in the riser, on flat floor and in straight or curved rows.

All fixings in chair are metal to metal and floor fixed for every other chair.

## SEAT

Seatpad in cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 120 mm.

Smooth, quiet tip-up spring mechanism - N.T.I. approved according to ISO 7173, Level 5 (highest level).

Upholstery sewn to measurements and easily removable with zipper solution.

## SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness 110 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

## ARMREST

Cold moulded polyurethane foam with integrated steelframe, optional widths 50, 70, 110, 140 mm.

Cupholder or table fixed to steelframe of armrest available.

Hana armrests in wood, width 70, 80, 100, 120 mm for C/C 550, 560, 580, 600 mm.

Available with wood armrests and sidepanels for row-end chairs, and without sidepanels for middle seats.

## ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Foldable writing tablet in armrest, Notis A, 12 mm plywood w/ laminate top available.

Row and seatnumbers are available.

Other qualities and measurements are available upon request.