

Skeie | Solist Tip-Up™

TECHNICAL SPECIFICATION

DIMENSIONS

Low back, 915 mm: C/C 560, 580, 600, 630 mm.
High back, 1040 mm: C/C 560, 580, 600, 630 mm.

FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 60 x 40 x 3 mm.

Standard floor fixing: 240 x 156 x 7 mm steelbracket fixed to the rear of the tread.

Powder coated steel in standard RAL colors.

Floor fixing every other chair.

The chair is suitable for fixing in the riser, on flat floor and in straight or curved rows.

All fixings in chair are metal to metal and floor fixed for every other chair.

SEAT

Seatpad in cold moulded polyurethane foam w/ integrated 19 x 2 mm steel frame, thickness 110 mm.

Smooth, quiet tip-up spring mechanism - N.T.I. approved according to ISO 7173, Level 5 (highest level).

Upholstery sewn to measurements and easily removable with zipper solution.

SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steel frame, thickness 110 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Cold moulded polyurethane foam with integrated steel frame, optional widths 70, 90, 110 mm.

Cupholder or table fixed to steel frame of armrest available.

ADDITIONAL SPECIFICATIONS

Row and seat numbers are available.

Other qualities and measurements are available upon request.