

## Skeie | Epic™

TECHNICAL SPECIFICATION

### DIMENSIONS

High back, ca 1090 mm: C/C 640 mm.

### FRAME CONSTRUCTION

ST-37 steel alloy.  
Powder coated steel in standard RAL 9005.  
Floor fixing on each armrest.  
Fixing in straight or curved rows.  
Max load motors 1500Nm, TÜV certificated.  
Low noise electrical reclining mechanism for seat, back and footrest.

### SEAT

Polyurethane foam w/ integrated 19 x 2 mm internal steel frame.  
Upholstery sewn to measurements and easily removable with zipper solution.  
Good seat support and comfortably.

### BACK

Polyurethane foam with integrated 19 x 2 mm steel frame.  
Upholstery sewn to measurements and easily removable with zipper solution.  
Comfortable lumbar support and side support.

### ARMREST

Plywood with foam cover - 45mm on top, 10mm front and side armrest.  
Steel frame inside for frame connection.  
Medium height to fit the average of people, comfortably density of foam.

### ALTERNATIVE W/ TABLE

Wood tabletop fixed in front of armrest.  
Standard width is 110mm, which can be adjusted based on requirements.  
Cup-holders available.

### ADDITIONAL SPECIFICATIONS

Row and seat-numbers are available. Reading light, USB outlet, wireless charger in table, cleaning light under seat, etc..  
Other qualities and measurements are available upon request.

