

Skeie | Epic Tip-Up™

TECHNICAL SPECIFICATION

skeie®

Skeie Seating AS,
Svanholmen 19
N-4313 Sandnes, Norway

E: seating@skeie.com
www.skeie.com

Reg.No. NO913369947MVA

DIMENSIONS

High back, 1060mm: cc 560, 600m

Tip-up seat with standard, closed or damped return mechanism.

FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 60 x 40 x 3 mm.

Standard floor fixing: 240 x 156 x 7 mm steelbracket fixed to the rear of the tread.

Powder coated steel in standard RAL colors.

The chair is suitable for fixing in the riser, on flat floor and in straight or curved rows.

All fixings in chair are metal to metal and floor fixed for every other chair.

SEAT

Cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 120mm.

Upholstery sewn to measurements and easily removable with zipper solution.

SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness center profile max/min 110/65mm.

Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Cold moulded polyurethane foam with integrated steelframe, optional widths are 70 and 110mm.

Cupholder or table mounted to steelframe on armrest available.

ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Row and seatnumbers are available.

Can be delivered without the reclining functionality.

Other qualities and measurements are available upon request.